

In the Claims:

Amend the claims as follows:

- 5
1. (Currently amended) ~~Method~~ A method for sending messages over secure communication links in networks comprising at least a first terminal being able to change its method of network access and at least one other terminal with one or
- 10 more possible intermediate computers between the first terminal and the other terminal performing network address and/or other translations, a secure communication link being established between an initial network address of the first terminal and the address of the other terminal, the link
- 15 defining at least the addresses of the two terminals, and performing encapsulation in said secure communication link to overcome network address and/or other translations made by said intermediate computers on the route, comprising:
- ~~characterized by~~
- 20 a) the first terminal moving from said initial network address to a new network address,
- b) sending a request message using encapsulation from the first terminal to the other terminal to change said secure connection to be between the new address of the first terminal
- 25 and the other terminal, the request also containing a description of the encapsulation method performed by the first terminal on the basis of which description the other terminal detects translations performed by said intermediate computers,
- c) the other terminal responding to the first terminal with a
- 30 reply message with a description about translations made by said possible intermediate computers between the new address of the first terminal and the other terminal and/or encapsulation methods supported by the other terminal, and
- d) thereafter sending the message from the first terminal to
- 35 the other terminal by using the information sent with said

reply.

2. (Currently amended) ~~Method of claim 1, characterized in that,~~ The method of claim 1 wherein the description of the message include source and/or destination addresses on the basis of which the receiving terminal detects address translations performed by intermediate computers.

3. (Currently amended) ~~Method of claim 1, characterized in that~~ The method of claim 1 wherein the description of the message includes information about encapsulation protocols, as well as source and destination TCP or UDP ports.

4. (Currently amended) ~~Method of claim 3, characterized in that~~ The method of claim 3 wherein the NAT traversal is performed by UDP encapsulation, TCP encapsulation and/or by ~~some other~~ another encapsulation.

5. (Currently amended) ~~Method of any of claims 1-4, characterized in that~~ The method of claim 1 wherein after receiving of the request message by said other terminal sent in step c), the other terminal determines by examining the request, which translations and/or encapsulations are required in the traffic between the first terminal and the other terminal.

6. (Currently amended) ~~Method of claim 5, characterized in that~~ The method of claim 5 wherein the reply message of step c) contains information about the communication link to be used between the new address of the first terminal and said other terminal.

7. (Currently amended) ~~Method of claim 6, characterized in that~~ The method of claim 6 wherein the information about the communication link includes information about

whether NAT traversal and/or other encapsulation should be used.

8. (Currently amended) ~~Method of any of claims 1-5,~~
 5 ~~characterized in that~~ The method of claim 1 wherein in step c)
 the first terminal compares the descriptions of the request
 respective reply messages and sends all subsequent messages
 from this new network address on the basis of the comparison
 telling what encapsulations, protocols and rules should be
 10 used in the further communication.

9. (Currently amended) ~~Method of any of claims 1-8,~~
~~characterized in that~~ The method of claim 1 wherein the secure
 communication link is formed by using the IPSec protocol.

15 10. (Currently amended) ~~Method of claim 9, characterized in~~
~~that~~ The method of claim 9 wherein the message in step d) is
 sent by using IPSec and NAT traversal updated to the new
 network address of the first terminal.

20 11. (Currently amended) ~~Method of claims 7 or 8, characterized~~
~~in that~~ The method of claim 1 wherein the message in step d)
 is sent without NAT traversal in the communication link ~~if on~~
~~the basis of the comparison in claim 8, when~~ the descriptions
 25 correspond to each other ~~or if so informed by the other~~
~~terminal in claim 7.~~

12. (Currently amended) ~~Method of any of claims 1-11,~~
~~characterized in that~~ The method of claim 1 wherein the secure
 30 connection is an IPSec SA.

13. (Currently amended) ~~Method of claim 12, characterized in~~
~~that for forming the IPSec SA,~~ The method of claim 12 wherein
 a key exchange mechanism that passes through NAT is used when
 35 forming the IPSec SA.

14. (Currently amended) ~~Method of claim 12, characterized in that~~ The method of claim 12 wherein the key exchange protocol is IKE ~~if~~ when the NAT device supports the UDP protocol.

5

15. (Currently amended) ~~Method of claim 14, characterized in that for forming the IPSec SA,~~ The method of claim 14 wherein a key exchange mechanism is used when forming the IPSec SA and wherein several traversal mechanisms are used simultaneously to increase the chance that at least one of them pass through the NAT device.

10

16. (Currently amended) ~~Method of claim 12, characterized in that for forming the IPSec SA,~~ The method of claim 12 wherein a key exchange mechanism is performed when forming the IPSec SA in which a negotiation process is used to agree on protocols to be used in the further communication.

15

17. (Currently amended) ~~Method of claim 12, characterized in that~~ The method of claim 12 wherein for forming the IPSec SA, an encapsulation protocol is used in the key exchange mechanism when forming the IPSec SA.

20

18. (Currently amended) ~~Method of any of claims 1 - 17, characterized in that~~ The method of claim 1 wherein the address of the other terminal is the end destination address of messages sent from the first terminal, in which case transport or tunnel mode is used in the IPSec communication.

25

19. (Currently amended) ~~Method of any of claims 1 - 17, characterized in that~~ The method of claim 1 wherein the destination address of the message is the address of a host which is not the other terminal, in which case tunnel mode or transport mode together with a tunnelling tunneling protocol is used in the IPSec communication.

30

35

20. (Currently amended) ~~Method of any of claims 1-7, 9-19,~~
~~characterized in that~~ The method of claim 1 wherein several
 request messages of step b) are sent, each processed using a
 5 different traversal mechanism, where after the other terminal
 indicates in the reply which methods is to be used in the
 further-communication.

10